



7 inch Full HD Camera Monitor

High Resolution: 1920x1200
High Brightness: 300cd/m²
High Contrast: 1800:1

• Support HDMI, 4K HDMI

• H/V Flip, DSLR Scaling, Clip Guide

• Underscan, Audio meters, Pixel to Pixel












king Zooming False Color Histogram Pixel to Pixel



PRODUCT DESCRIPTION





- 1. DC 7-24V
- 2. Earslot
- 3. USB Input (for Customer to upgrade locally)
- 4.1/4-20 Threaded Insert
- 5. HDMI Out
- 6. HDMI In
- 7. ¼-20 Threaded Insert
- 8. Power
- 9. F1 (custom)
- 10. F2 (custom)
- 11. 1/4-20 Threaded Insert
- 12. Power Light
- 13. Exit
- 14. Menu
- 15. 1/4-20 Threaded Insert

FEATURE

- Peaking FilterLow Battery ALM
- H/V DelayColor Temperature
- Cross HairClip Guide
- 5D II Rec • Underscan
- Grids
- Audio Post

Peaking

The operator adjusts the focus control until the red outlines on the desired area are clear, indicating optimal focus. For the best results, be sure the subject is properly exposed. Enjoy taking your photos!



Subject in focus with Filter off



Subject in focus with Filter on



Subject out-focus with Filter off



Subject out-focus with Filter on





Check Field

Check field function has 4 modes: Mono,R,G,B.





Mono







Guides



Original



16:9 80%



16:9 90%





4:3




1.5:1





2:1





Custom(W:1%~100%)



Custom(H:1%~100%)

SPECIFICATIONS/ACCESSORIES

Format

Signal	
4096×2160p@24Hz	
3840×2160p@23.98,24,25,29.97,30Hz	
1920×1080p@23.98,24,25,29.97,30,50,59.94,60Hz	
1920×1080psf@23.98,24,25,29.97,30Hz	
1920×1080i@50,59.94,60Hz	
1280×720p@24,25,30,50,59.94,60 Hz	
720×576i@50 Hz	
720×576p@50 Hz	
720×480i@59.94,60 Hz	
720×480p@59.94,60 Hz	

Standard Accessories





Sunshade



Screen protection film



Lens cloth

Specifications

Mod	del No.	CT710HO
Pan	el	7"
Inpu	it&Output	HDMI (Support 4K HDMI)
Earp	ohone Jack	x1
Asp	ect Ratio	Full, 16:9, 15:9, 4:3, 1.5:1, 1.85:1, 2:1, 2.35:1, Custom(W: 50-100; H: 50-100)
H/V	Flip	Display flip mode and OSD flip mode
Colo	or Temperature	5600k,6500k,7500,9300, Custom
Rese	olution	1920x1200
Brig	htness	300cd/m²
Con	trast	1800:1
Viev	ving Angle	178°/178°(H/V)
Inpu	ıt Voltage	DC 7-24V(XLR)
Batt	ery Plate	V-mount/Anton Bauer mount
Pow	er consumption	7.5W
Dim	ension(LWD)	184x116x17mm
Wei	ght	0.26kg/1.5kg (with case)

Optional Accessories











• NWLP-E6 Type Battery Plate: For Canon 5D Batteries

• NWD54s Type Battery Plate: For Panasonic D54 Series Batteries • NWBP945 Type Battery Plate: For Canon "900" Series Batteries

• NWEN-EL15 Type Battery Plate: For Nikon D700 / D800 etc camera Series Batteries



USB flash disk

battery plate (LP-E6)

[•] NWNP-F960 Type Battery Plate: For Sony "L" Type Series Batteries